



**Address:** 8 Manburgh Terrace  
Darra Qld. 4076  
**Postal Address:** P.O. Box 3045  
Darra Qld. 4076  
**Phone:** +61 (7) 3375 3199  
**Facsimile:** +61 (7) 3375 3886  
**E-mail:** info@luxurypaints.com.au

Date Issued: 1 December, 2011  
Page 1 of 2

**LP0006**

## EASICLEAN SILK LOW SHEEN

**Product Line:** 14

**Product Code:** 1401; 1402; 1404; 1410; 1420; 14XX01; 14XX02; 14XX04; 14XX10; 14XX20 where XX represents digits for colour codes.

### Description

Easiclean Silk Low Sheen is premium quality, 100% acrylic, washable silk sheen paint finish designed for heavy traffic areas.

### Features

Water based  
100% acrylic paint  
High opacity  
Easy to apply, high opacity, extremely washable, suitable for use in wet areas.

### Benefits

Same day recoat and easy clean up  
Proven excellent durability which maximizes time before recoat  
Assured hiding minimizes labour

### Uses

Suitable for use where a premium, washable, low sheen finish is required. Used on correctly prepared plaster, wallboard, fibrous cement, plaster, brick and primed interior timber on walls and ceilings in kitchens, bathrooms, bedrooms, living rooms etc.

### Typical Specifications

Surface	Preparation	System	Dry Film Thickness
Timber (New timber)	Remove any contaminants. Sand to smooth surface.	First Coat: Speed Prep Sealer Primer Undercoat	30 - 40µm
		Top Coat: 2 coats Easi Clean Interior (int.)	50 - 60µm
Plasterboard	Fill joints. Remove sanding dust.	First Coat: Speed Prep Sealer Primer Undercoat	30 - 40µm
		alternatively Easi Sealer Undercoat Top Coat: 2 coats Easi Clean Interior	50 - 60µm
Masonry, brick, concrete blockwork, fibre cement board	Remove any contaminants.	First Coat: Speed Prep Sealer Primer Undercoat	30 - 40µm
		alternatively Easi Sealer Undercoat Top Coat: 2 coats Easi Clean Interior	50 - 60µm

### Surface Preparation

All surfaces must be well prepared and free from dirt, oil, grease and other contaminants.

#### NEW UNPAINTED SURFACES

Fill any nail holes, cracks and surface imperfections with appropriate patching material. Sand and dust area ensuring the surface is clean and dust free. Seal plaster surfaces with Easi Sealer Undercoat. Apply 1 coat of Speedprep Primer Sealer Undercoat on interior timber. Allow surface to dry before applying 2 coats of Easiclean Silk Low Sheen.

#### PREVIOUSLY PAINTED SURFACES

Remove all loose and flaking paint. Wash down all chalky surfaces and leave to dry for approximately 2 hours. Apply 1 coat of Speedprep Primer Sealer Undercoat to bare sanded areas. Allow surface to dry before applying 2 coats of Easiclean Silk Low Sheen.



**Address:** 8 Manburgh Terrace  
Darra Qld. 4076  
**Postal Address:** P.O. Box 3045  
Darra Qld. 4076  
**Phone:** +61 (7) 3375 3199  
**Facsimile:** +61 (7) 3375 3886  
**E-mail:** info@luxurypaints.com.au

**Date Issued:** 1 December, 2011  
Page 2 of 2

**LP0006**

## Application Method

Stir contents of can thoroughly with a wide flat stirrer ensuring the bottom of the can is reached. Apply a full coat of Easiclean Silk Low Sheen by brush, roller or spray.

Do not apply Easiclean Silk Low Sheen below 12 deg. C (or is likely to fall below 12 deg. C) before the paint can dry thoroughly.

### Brush/Roller

Pre-wet brushes and rollers. Flow paint generously and spread evenly - do not overspread. Use a quality bristle brush or a medium 12mm-nap roller cover for best results. On rough surfaces, use a 20mm-nap roller cover. Avoid excessive brushing or rolling.

### Spray

Suitable for application using standard spray equipment. If necessary, Easiclean Silk Low Sheen may be thinned sparingly with up to 100mls of water per litre of paint to help atomization.

### Thinning

Not usually required, however it may be thinned sparingly with water.

## Approximate Coverage

Covers approximately 14-16 square metres per litre depending on the surface porosity.

## Colours Available

Available in white and a full range of machine tinted colours.

## Drying Times

Approximate drying times at 25°C and 50% Relative Humidity.

Touch Dry:	30 minutes
Recoat:	Minimum 2 hours.

Drying times may be extended by adverse drying conditions or very high film build.

## Cleanup

Clean all equipment promptly with water.

## Properties

SOLIDS BY VOLUME:	35%
SOLIDS BY WEIGHT:	52%
WEIGHT PER LITRE:	1.4kg
GLOSS LEVEL:	10%
DURABILITY:	Excellent - interior, washable, hard wearing finish.
VOC:	approximately 52 grams per litre

## Resistance Properties

ABRASION:	Very Good.
HEAT:	Good. May soften at elevated temperatures.
SOLVENT:	Poor. Is sensitive to aromatic hydrocarbons, alcohols and ketones.
WATER/STEAM:	Good. Suitable for wet areas.
WEATHER:	For interior use only.

## Additional Information

Allow 7 days for the paint film to cure before scrubbing the surface. Allow 48 hours drying time before exposing to light steam and condensation.