



**SAFETY DATA SHEET
EASICLEAN SILK**

Date Issued: 1 May, 2012
LP0006

Page 1 of 8

***1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING**

1.1 Product Identifier:

Product Name: **EASICLEAN SILK**

Product Line: 14 Series

Product Code: 1401;1402; 1404; 1410; 1420; 14XX01; 14XX02; 14XX04; 14XX10; 14XX20 where XX represents digits for colour codes.

CAS No: Not Applicable

1.2 Relevant identified uses of the substance or mixture and uses advised against

Brushing, rolling, spraying grade of architectural water based acrylic interior low sheen wall paint.

1.3 Details of the supplier of the Safety Data Sheet

Company Identification: Luxury Paints Pty Ltd ABN 85 465 041 603
8 Manburgh Terrace, Darra, Brisbane Qld, 4076 Australia
PO Box 3045 Darra Qld, 4076 Australia

Telephone: +61 (7) 3375 3199
Fax: +61 (7) 3375 3886
Email: info@luxurypaints.com.au

1.4 Emergency telephone number

Emergency Phone No. A/H: mob.: 0413 949 709

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

According to Regulation (EC) N. 1272/2008 (CLP)

Non-hazardous

2.2.1 Label elements

Not Applicable

Signal word(s):

Not Applicable

Hazard statement(s):

Not Applicable

Precautionary statement(s):

P102: Keep out of reach of children.
P301 + P310 IF SWALLOWED: Immediately call a POISON CENTRE or doctor/physician
P304 + P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

2.2.2 Label elements

According to Directive 67/548/EEC & Directive 1999/45/EC

Hazard pictogram(s):

Not Applicable

Hazard Symbol:

Not Applicable

Risk Phrases:

R36/37/38: Irritating to eyes, respiratory system and skin.
R65: Harmful: May cause lung damage if swallowed.

Safety Phrases

S2 Keep out of the reach of children.
S3/7/9 Keep container tightly closed in a cool, well ventilated place.
S24/25 Avoid contact with skin and eyes.

2.3 Other hazards

Not applicable.



SAFETY DATA SHEET
EASICLEAN SILK

Date Issued: 1 May, 2012
 LP0006

3.3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances
 EC Classification No. 1272/2008

Hazardous ingredient(s)	% w/w	CAS No.	EC No.	Hazard symbol(s) and hazard statement(s)
Nil hazardous ingredients				
Acrylic co-polymer emulsion	30 - ≤ 60	Not regulated		Not Applicable
Titanium dioxide	0 - ≤ 30	13463-67-7		
Pigments – non-hazardous	0 - ≤ 30	Various		
Filler pigments , non regulated	10 - ≤ 30	Various		
Propylene glycol	1 - ≤ 10	57-55-6		
Preservative – non formaldehyde type	1 - ≤ 10			
Additives	Various	Various		
Water	To 100%	7732-18-5		

EC Classification No. 67/548/EC

Hazardous ingredient(s)	% w/w	CAS No.	EC No.	Risk Phrases and Safety Phrases
Nil hazardous ingredients				
Acrylic co-polymer emulsion	30 - ≤ 60	Not regulated		Not Applicable
Titanium dioxide	0 - ≤ 30	13463-67-7		
Pigments – non-hazardous	0 - ≤ 30	Various		
Filler pigments , non regulated	10 - ≤ 30	Various		
Propylene glycol	1 - ≤ 10	57-55-6		
Preservative – non formaldehyde type	1 - ≤ 10			
Additives	Various	Various		
Water	To 100%	7732-18-5		

4. FIRST AID MEASURES

For advice, contact Poisons Information Centre (Phone Australia: 1311 26) or a doctor.

4.1 Description of first aid measures

Inhalation: Remove patient from exposure, keep warm and at rest.

Skin Contact: Wash affected with soap and water or suitable skin cleansing cream. Remove contaminated clothing, including shoes, and launder before reuse. Seek immediate medical attention.

Eye Contact: Flush eyes with large amounts of water until irritation subsides. Seek immediate medical attention.

Ingestion: If swallowed, and if more than 15 minutes from a hospital or medical centre induce vomiting preferably using Ipecac Syrup APF. Keep at rest. Seek immediate medical attention. **DO NOT INDUCE VOMITING IN AN UNCONSCIOUS PERSON.**

4.2 Most important symptoms and effects, both acute and delayed Irritating to skin.

4.3 Indication of the immediate medical attention and special treatment needed Provide eye baths and safety showers.
 First Aid facilities: Treat according to symptoms.



SAFETY DATA SHEET
EASICLEAN SILK

Date Issued: 1 May, 2012
LP0006

Page 3 of 8

5. FIRE FIGHTING MEASURES

5.1 Extinguishing media

Suitable Extinguishing Media: This product is not flammable unless strongly heated in an existing fire. Use extinguishing media for surrounding burning material.

Unsuitable Extinguishing Media: Determined by surrounding burning material.

5.2 Special hazards arising from the substance or mixture

None known. May give off carbon monoxide and carbon dioxide when strongly heated in a fire.

5.3 Advice for fire-fighters

A self-contained breathing apparatus and suitable protective clothing should be worn in fire conditions. Keep fire exposed containers cool by spraying with water.
Prevent extinguishing media from escaping to drains and waterways.
Hazchem Code: None.

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Avoid inhalation of vapours. Avoid contact with skin and eyes. Wear suitable protective clothing and gloves. (See Section: 8)
Contaminated clothing should be thoroughly cleaned.

6.2 Environmental precautions

Do not allow to enter drains, sewers or watercourses. Spillages or uncontrolled discharges into watercourses must be alerted to the Environmental Agency or other appropriate regulatory body.

6.3 Methods and material for containment and cleaning up

Adsorb spillages onto sand, earth or any suitable absorbent material. Sweep up and transfer to a container for disposal. Wash spill area with soapy water. Contaminated absorbent must be removed in sealed, plastic lined drums and disposed of via an authorized waste disposal contractor.

6.4 Reference to other sections

Personal Protection: See Section: 8

Other advice

Caution – spillages may be slippery.

7. HANDLING AND STORAGE

7.1 Precautions for safe handling

This product is non-flammable. Keep container closed. Handle containers with care. Open slowly to control possible pressure release. Avoid contact with skin and eyes. Wear suitable protective clothing and gloves. (See Section: 8)

Do not eat, drink or smoke at the work place. Wash hands and exposed skin after use. Contaminated clothing should be thoroughly cleaned.

7.2 Conditions for safe storage, including any incompatibilities

Keep away from direct sunlight. Keep away from frost. Keep only in the original container in a cool, well-ventilated place. Keep/store away from: Acids and Oxidizing agents.

7.3 Specific end use(s)

Industrial use only.



SAFETY DATA SHEET
EASICLEAN SILK

Date Issued: 1 May, 2012
LP0006

Page 4 of 8

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

National Exposure Standards

The time weighted average concentration (TWA) for this product is: None specified - which means the highest allowable exposure concentration in an eight-hour day for a five-day working week. The short-term exposure limit (STEL) is: None specified, which is the maximum allowable exposure concentration at any time.

8.2 Exposure Controls

8.2.1 Appropriate engineering controls

Provide adequate ventilation, including appropriate local extraction, to ensure that the occupational limit is not exceeded.

8.2.2 Personal protection

Eye/ face protection

Goggles giving complete protection to the eyes. (EN 166)

Skin protection

Protective gloves.

Respiratory protection

In case of insufficient ventilation, wear suitable respiratory equipment.

Other

Apron or other light protective clothing, boots and plastic or rubber gloves.

8.2.3 Environmental Exposure Controls

Avoid release to the environment.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance	Coloured liquid
Odour	Mild slightly ammoniacal
Melting Point (°C)/ Freezing Point (°C)	0°C (Water)
Boiling Point (°C)	100°C (Water)
Flash point (°C)	Non-flammable
Flammable Limits (Lower) (°C)	Non-flammable
Flammable Limits (Upper) (°C)	Non-flammable
Vapour Density @ 20°C (kPa)	Not available
Density @ 25°C	1.20 – 1.50
Solubility in water (% w/w)	Miscible
Auto-ignition Temperature (°C)	Not applicable
Viscosity @ 25°C (Seconds)	Not applicable
Explosive Properties	Not applicable
Oxidising Properties	Not oxidising

9.2 Other information

Percent volatiles (% v/v) 40 – 60



SAFETY DATA SHEET

EASICLEAN SILK

Date Issued: 1 May, 2012

LP0006

Page 5 of 8

10. STABILITY AND REACTIVITY

10.1 Reactivity

Reacts with oxidizing agents, mineral acids, halogenated organic compounds.

10.2 Chemical stability

Stable under normal conditions of use.

10.3 Possibility of hazardous reactions

No information available.

10.4 Conditions to avoid

Keep away from heat and direct sunlight.

10.5 Incompatible materials

Oxidizing agents, mineral acids, halogenated organic compounds

10.6 Hazardous Decomposition Product(s)

May give off toxic fumes in a fire when strongly heated.

Carbon monoxide and carbon dioxide.

No hazardous decomposition products when stored and handled correctly except on burning. See FIRE FIGHTING MEASURES; Section: 5

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity:

Ingestion:

No information available.

May cause irritation to the throat, mouth and digestive tract.

Large doses may cause drowsiness and may lead to unconsciousness.

Aspiration of liquid into lungs may cause serious (even fatal) pneumonitis.

Inhalation:

No information available.

Vapour is irritating to mucous membranes and respiratory tract.

Can cause dizziness, headaches, nausea and may lead to unconsciousness.

Prolonged exposure to vapour may cause damage to the central nervous system.

Skin Contact:

No information available.

Irritant, both by contact and vapour. Prolonged exposure may result in dryness and cracking.

Eye Contact:

No information available.

Irritant, both by contact and vapour.

Other information:

Chronic:

Principal routes of exposure are usually by skin contact with the material and inhalation of vapour/ spray mist. Prolonged or repeated skin contact may cause drying and/or cracking with irritation and possible dermatitis following. As with any chemical product, contact with unprotected bare skin; inhalation of vapours, mist or dust in a work place environment; or ingestion in any form should be avoided by observing good occupational work practices.

Advice to Doctor: Treat symptomatically.



SAFETY DATA SHEET

EASICLEAN SILK

Date Issued: 1 May, 2012

LP0006

Page 6 of 8

12. ECOLOGICAL INFORMATION

12.1 Toxicity

Fish Toxicity (rainbow trout, goldfish, and bluegill)
LC₅₀ (96 hr): Based on data for similar components or preparations, this product is expected to be toxic to aquatic organisms.

12.2 Persistence and degradability

Daphnia Magna EC₅₀ (48 hr): Long term adverse effects to aquatic organisms are possible if continuous exposure is maintained.
Remark: On the basis of the data for ecotoxicological effects, the substance can be classified as non-critical to aquatic organisms in the water-soluble range. As the substance is not readily biodegradable, long retention times in water are to be expected. This applies only in cases where no other elimination mechanisms (photodegradation, hydrolysis, adsorption) are active. However, as there is no ecotoxic effect, no damage to the ecosystem is to be expected. Do not allow to escape into waterways, waste water or soil.

12.3 Bioaccumulative potential

No information available.

12.4 Mobility in soil

No information available.

12.5 Results of PBT and VPVB assessment

No information available.

12.6 Other adverse effects

No information available.

13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Do not empty into drains; dispose of this material and its container in a safe way.

The relevant local, regional and national regulations must be complied with. It is among the tasks of the polluter to assign the waste to waste codes specific to industrial sectors and processes according to the national authority. It is recommended that details be worked out with the waste disposal company responsible.

The waste can be disposed of in a suitable incinerator or approved landfill site, provided that national/ local legislation is complied with.

After final product withdrawal, all residues must be removed from containers (drip-free, powder-free or paste-free). Once the product residues adhering to the walls of the containers have been rendered harmless, the product and hazard labels must be invalidated. Containers must be recycled in compliance with national and environmental regulations.



SAFETY DATA SHEET
EASICLEAN SILK

Date Issued: 1 May, 2012
LP0006

Page 7 of 8

14. TRANSPORT INFORMATION

14.1 UN Number	None assigned
14.2 Proper Shipping Name	PAINT
14.3 Transport hazard class(es)	None
14.4 Packing Group	None
14.5 Environmental hazards	None known
14.6 Special precautions for user	None known
14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	None known

Other information: Keep dry. Keep separated from foodstuffs.

15. REGULATORY INFORMATION

According to Regulation (EC) No. 1272/2008 (CLP)

Hazard pictogram(s):	None
Signal word(s)	Warning
Hazard statement(s)	Not Applicable
Precautionary statement(s)	P102: Keep out of reach of children. P301 + P310: IF SWALLOWED: Immediately call a POISON CENTRE or doctor/physician P304 + P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

According to Directive 67/548/EEC & Directive 1999/45/EC

Hazard pictogram(s):	None
Hazard Symbol:	None
Risk Phrases:	R22: Harmful if swallowed. R36/37/38: Irritating to eyes, respiratory system and skin. R65: Harmful: May cause lung damage if swallowed. R66: Repeated exposure may cause skin dryness and cracking. R67: Vapours may cause drowsiness and dizziness.
Safety Phrases:	S2: Keep out the reach of children. S3/7/9: Keep container tightly closed in a cool, well ventilated place. S24/25: Avoid contact with skin and eyes. S51: Use only in well ventilated areas. S62: If swallowed, and more than 15 minutes from hospital or a medical centre induce vomiting: seek medical advice immediately and show this container or label.

Not a scheduled poison under SUSDP.
Labeling as required by Chemicals (Hazard Information and Packaging for Supply) Regulations 2002 (CHIP3), in accordance with Australian requirements.
Symbol: Xi, Hazard description: Irritant



SAFETY DATA SHEET
EASICLEAN SILK

Date Issued: 1 May, 2012
LP0006

Page 8 of 8

16. OTHER INFORMATION

All components of this product are listed in the European Inventory of Existing Commercial Substances (EINECS) under the provisions laid down in the corresponding EC-Directive. The components are also listed in the Australian Inventory of Chemical Substances (NICNAS).

This Safety Data Sheet replaces all previous information.
Revised and valid from: see Date of Issue.

The data given here is based on current knowledge and experience. The purpose of this Safety Data Sheet is to describe the products in terms of their safety requirements. The above details do not imply any guarantee concerning composition, properties or performance.

End of Report.